

Open Top Container

Bulk Minerals, Heavy Machinery, Crane or Loading Bridge Loaded Cargo

This container primarily carries bulk minerals and heavy machinery.

Similar to general purpose containers, the floor and side walls are solid. However, a removable tarpaulin roof and roof bows replace the rigid roof. This design is ideal for cargo loaded using a crane or rolling bridge.



	20' x 8 x 8'6"	40' x 8' x 8'6"
<i>Size and Type Grouping Code</i>	20OT	40OT
<i>Dimensions and Type Code</i>	22U1	42U1
<i>Internal Dimensions</i>		
Length (mm)	5 898	12 032
Width (mm)	2 352	2 352
Height (mm)	2 348	2 348
<i>Door Opening</i>		
Width (mm)	2 340	2 340
Height (mm)	2 280	2 280
Height under top-rail (mm)	2 200	2 200
<i>Top Opening Dimensions</i>		
Length between end lintels (mm)	5 682	11 806
Width between gussets (mm)	1 840	1 650
Length between end gussets (mm)	5 397	11 531
Width between roof rails (mm)	2 252	2 232
Width between removable lintel (mm)	1 940	1 940
<i>Nominal Capacity (M³)</i>	32	66
<i>Maximum Gross Weight (kg)</i>	30 480	30 480
<i>Average Tare (kg)</i>	2 200	3 880
<i>Maximum Payload (kg)</i>	28 280	26 600
<i>Securing Rings</i>		
Quantity	20	40
Resistance (kg/ring)	1 500	1 500